



MEGAHAMMER®

KTI-70390 (3-Piece Set)

Removes seized bearing assemblies and associated components from a vehicle chassis for maintenance and repair. Minimizes cost and potential damage. Compatible with 3/4 and 1 ton American made trucks with 4, 6 or 8 bolt patterns. Complete MEGAHAMMER™ kit includes 4-6-8 bolt head (KTI-70394), slide and stop assembly (KTI-70395) and hammer assembly (KTI-70396). 38" length, 65 lbs. Additional optional head available.

Replacement Slide and Stop Assembly
KTI-70395

Replacement Hammer Assembly
KTI-70396



MEGAHAMMER® 5 Bolt Head

KTI-70391

Serves 1/2 ton Ford, GM and Dodge trucks. 8" diameter, 17½ lbs.



MEGAHAMMER® 8 Bolt Head

KTI-70392

Serves Ford Super Duty F250/F350 4x4 trucks. 8" diameter, 28½ lbs.



MEGAHAMMER® 6 Bolt Head

KTI-70393

For use primarily with Dodge Durango and Chevy Trailblazer. It will, however, accommodate any 6 bolt patterns with bolt circle diameters from 4" up to 6.75".



MEGAHAMMER® 4-6-8 Bolt Head

KTI-70394

Serves 3/4 and 1 ton American made trucks with 4, 6 or 8 bolt patterns. 8" diameter, 17½ lbs.



MEGAHAMMER® 4 Bolt Head

KTI-70397

Primarily for use with Honda vehicles with 4 bolt patterns. It will accommodate 4 bolt patterns with bolt circle diameters from 4.2" up to 5.26".





WARNING: Please follow instructions carefully to reduce risk of personal injury or possible damage to the vehicle.

CAUTION: Lock nut on hub removal tool must be tight to protect against thread damage. Slide shaft thread to be engaged into base plate thread so it is flush with inside edge of base plate thread. Use countersunk holes **ONLY** for proper grip on studs. Use outboard support to help prevent tool and wheel assembly from dropping to floor. Do not stand behind tool when in use. Tool is heavy. Use extreme caution when lifting. Keep extremities clear of pinch points. Always wear eye protection when using hub removal tool. Locking pin must be in place when not in use. Not responsible for damage to vehicle.